

IN THE SPECIFICATION

Page 1, before the first line, add the paragraph:

This is a divisional application of U.S. Serial No. 09/789,625, filed February 22, 2001.

IN THE ABSTRACT

Please rewrite the Abstract as follows:

~~In order to provide an automatic analyzer capable of ensuring an effective agitation of the reagent and specimen, hence, highly reliable results of analysis, despite small size of the reaction vessel, without carry-over among different specimens, a multiple~~Multiple piezoelectric elements 35 are arranged in a row along the ~~height~~top of liquid level in the reaction vessel 11, ~~and an~~ An ultrasonic reflecting material 38 is installed on the bottom of the portion of the heat insulating bath 12 where heat insulating medium 13 is stored. ~~Lateral~~A lateral ultrasonic wave 9b is generated on the lower side is generated by actuation of the piezoelectric element 35 ~~for lateral irradiation located at the bottom. Lateral ultrasonic wave~~Wave 9b is reflected by the ultrasonic reflecting material 38, ~~and, as~~ As a lower ultrasonic wave 8, advances along the wall surface of the reaction vessel, ~~to it~~ it collides with the specimen liquid level, thereby causing a ~~part~~portion of the liquid level ~~being~~ closer to the piezoelectric element 35 to be raised. When the lateral

ultrasonic wave 9a is applied to this portion, ~~lateral~~  
~~ultrasonic wave 9a~~ it reaches the inclined portion of the  
raised liquid level of the specimen. Swirling flow by  
agitation 36, ~~with specimen liquid level as a starting point,~~  
is produced by the acoustic radiation pressure of the  
ultrasonic wave. The specimen and reagent are mixed and  
agitated by ~~said~~this swirling flow ~~by agitation 36. This raise~~  
~~of the part of the liquid level is obtained by controlling a~~  
~~position and an angle of the lower ultrasonic wave 8.~~